Structures XML

```
<?xml version="1.0" encoding="ISO-8859-1" ?>
```

```
<bibiotheque>
 <livre nom="Guerre et paix"
   auteur="Léon Tolstoï"
   genre="roman" />
 <livre nom="Fondation"
   auteur="Isaac Asimov"
   genre="science-fiction" />
 <livre nom="La nuit du renard"
   auteur="Mary Higgins Clark"
   genre="policier" />
</bibiotheque>
```

```
<bibiotheque>
 <livre>
   <nom>Guerre et paix</nom>
   <auteur>Léon Tolstoï</auteur>
   <genre>roman</genre>
 </livre>
 <livre>
   <nom>Fondation</nom>
   <auteur>Isaac Asimov</auteur>
   <genre>science-fiction</genre>
 </livre>
 <livre>
   <nom>La nuit du renard</nom>
   <auteur>Mary Higgins Clark</auteur>
   <genre>policier</genre>
 </livre>
</bibiotheque>
```


Structures XML

```
<groupes>
 <groupe id="1" name="Groupe Collaboratif 1">
  <membres>
   <membre nom="Durand" prenom="Jean-Paul" />
   <membre nom="Dupond" prenom="Daniel" />
  </membres>
 </groupe>
 <groupe id="2" name="Groupe Collaboratif 2">
  <membres>
   <membre nom="Martin" prenom="Jean" />
   <membre nom="Grosjean" prenom="Michel" />
   <membre nom="Marchal" prenom="Jérémie" />
  </membres>
 </groupe>
</groupes>
```



```
<?xml version="1.0" encoding="ISO-8859-1" ?>
<xsl:stylesheet version="1.0" xmlns="http://www.w3.org/1999/XSL/Transform">
 <xsl:template match="xml">
  ...
  <xsl:apply-templates select="./balises/balise" />
  <xsl:call-template name="toto" />
  ...
 </xsl:template>

 <xsl:template match="balise">
  ...
 </xsl:template>

 <xsl:template name="toto">
  ...
 </xsl:template>
</xsl:stylesheet>
```

XSLT